

High Resolution IR Dome Camera with OSD - 20 Mtr.



Main Features

- ⇒ 1/3" SONY Super HAD II CCD
- ⇒ 540 TVL High Resolution Camera
- ⇒ 0 LUX/F1.2(IR ON)
- ⇒ IR Range of 20M with 24 pcsΦ5 LEDs
- ⇒ 3.6 mm Lens
- ⇒ OSD, D-WDR, DNR, Motion Dection, Privacy Masking, Mrror, AWB, AGC, BLC
- ⇒ CE, FCC and RoHS Certified



Feature	Specification
Image Sensor	1/3" SONY Super HAD II CCD
Pixels	PAL:500 (H)x582(V)
Resolution	540 TVL
Min. Illumination	0 LUX/F1.2(IR ON)
S/N Ratio	more than 48 dB(AGC OFF)
Electronic Shutter	1/50(60)sec-1/100,000sec
Lens	3.6 mm
Gamma Correction	0.45
White Balance (AWB)	ATW1 / ATW2 / MANUAL / AWC->SET / ANTI.CRL
Gain Control (AGC)	OFF /LOW / MID / HIGH
Back Light Compensation	BLC / HBLC / OFF
IR	IR Range of 20M with 24 pcsΦ5 LEDs
WDR	ON/OFF
Sync	Internal Sync
Video Output	Composite 1.0V P-P/75Ω
Special Functions	OSD, D-WDR, DNR, Motion Dection, Privacy Masking, Mrror
Power Supply	DC12V±10%
Power Consumption	<3W
IP Rating	IP60
Dimensions	112x87mm
Weight	260g
Operating Temperature	-10°C ~ 50°C/30%~80%RH
Certifications	CE & FCC