

DH-NVR4204/4208/4216/4232

4/8/16/32CH 1U Network Video Recorder



Features

- > Up to 4/8/16/32 channel with 1080P realtime live view
- > H.264/MJPEG dual codec decoding
- > Max 200Mbps incoming bandwidth
- > Up to 5Mp resolution preview&playback
- > HDMI/VGA simultaneous video output
- > 4/8/16 channel synchronous realtime playback, GRID interface
- > Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek and etc.
- > ONVIF Version 2.3 conformance
- > 3D intelligent positioning with Dahua PTZ camera
- > Support 2 SATA HDDs up to 8TB, 2 USB(1 USB3.0)
- > Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS

DH-NVR4204/4208/4216/4232


Technical Specifications

| Model | DH-NVR4204 | DH-NVR4208 | DH-NVR4216 | DH-NVR4232 |
|------------------------------------|---|------------|------------|------------|
| System | | | | |
| Main Processor | Dual-core embedded processor | | | |
| Operating System | Embedded LINUX | | | |
| Video | | | | |
| IP Camera Input | 4 channel | 8 channel | 16 channel | 32 channel |
| Two-way Talk | 1channel Input, 1channel Output, RCA | | | |
| Display | | | | |
| Interface | 1 HDMI,1 VGA | | | |
| Resolution | 1920×1080, 1280×1024, 1280×720, 1024×768 | | | |
| Display Split | 1/4 | 1/4/8/9 | 1/4/8/9/16 | 1/4/8/9/16 |
| OSD | Camera title, Time, Video loss, Camera lock, Motion detection, Recording | | | |
| Recording | | | | |
| Compression | H.264/MJPEG | | | |
| Resolution | 5Mp (2560×1920) /3Mp (2048×1536) /1080P(1920×1080) / 720P(1280×720) / D1 (704×576/704×480)&etc. | | | |
| Record Rate | 200Mbps | | | |
| Bit Rate | 48~ 8192kbps | | | |
| Record Mode | Manual, Schedule(Regular(Continuous), MD, Alarm), Stop | | | |
| Record Interval | 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec | | | |
| Video Detection & Alarm | | | | |
| Trigger Events | Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Buzzer & Screen tips | | | |
| Video Detection | Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank | | | |
| Alarm Input | 4 channel | | | |
| Relay Output | 2 channel | | | |
| Playback & Backup | | | | |
| Sync Playback | 1/4 | 1/4/9 | 1/4/9/16 | 1/4/9/16 |
| Search Mode | Time/Date, Alarm, MD & Exact search (accurate to second), Smart search | | | |
| Playback Function | Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom | | | |
| Backup Mode | USB Device/Network/Internal SATA burner | | | |
| Network | | | | |
| Ethernet | 1 RJ-45 port (10/100/1000Mbps) | | | |
| Network Function | HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, IP Search(Support Dahua IP camera, DVR, NVS and etc.) | | | |
| Max. UserAccess | 128users | | | |
| Smart Phone | iPhone, iPad, Android, Windows Phone | | | |
| Storage | | | | |
| Internal HDD | 2 SATA ports, up to 8TB, Raid (Redundancy) | | | |
| Auxiliary Interface | | | | |

DH-NVR4204/4208/4216/4232

| | |
|---------------------|--|
| USB | 2 ports (1 Rear USB3.0,1 Front USB2.0) |
| RS232 | 1 port, For PC communication&Keyboard |
| RS485 | 1 port, For PTZ control |
| General | |
| Power Supply | DC12V/4A |
| Power Consumption | 20W(without HDD) |
| Working Environment | -10°C ~+55°C / 10%~90%RH / 86~106kpa |
| Dimension (W×D×H) | 1U, 375mm×285mm×50mm |
| Weight | 2.0KG(without HDD) |

System Connection



*Takes NVR4216 as an example

Dahua Technology Co., Ltd.

1199'BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email: overseas@dahuatech.com

www.dahuatech.com

*Design and specifications are subject to change without notice.

© 2014 Dahua Technology Co., Ltd.