



**SSCCB574R**  
Outdoor Analog Fixed  
Camera with 9-22mm  
vari-focal lens.

**\$556.29**

U.S.List Price

UPC: 027242272750

**Overview**

Outdoor Analog Fixed Camera with 9-22mm vari-focal lens.

**Highlights**

- \* High Resolution 700TVL
- \* IP-66 Rated
- \* Built In IR (Working Distance 30 m (98 feet ) (50 IRE))
- \* 960H EXview HAD CCD II for high resolution and sensitivity
- \* Day/Night (Removable IR Cut Filter) function for improved visibility
- \* AC24/DC12 dual power supply

**Specifications**

Camera Specifications	Detail
IP/Analog	Analog
Image Device	1/3-type "EXview HAD CCD II"
Effective Pixels	480,000 (976 x 494)
Horizontal Resolution	700 TV lines (sharp mode) 650 TV lines (normal mode)
Minimum Illumination	Color: 0.09 lx, B/W: 0 lx (F1.2, 50 IRE) Color: 0.05 lx, B/W: 0 lx (F1.2, 30 IRE)
Lens Type	Built-in vari-focal lens
Focal Length	f=9mm to 22mm
F-Number	F1.4(Wide), F1.6(Tele)
Day Night	Yes(removable IR Filter)
Zoom Ratio	Optical 2.4x

Minimum Object Distance	39 3/8 inches (1000mm)
White Balance Mode	ATW (2000K to 10000K), ATW-PRO (2500K to 6000K)
Horizontal Viewing Angle	32.1° to 13.1°
Gain	Auto(On/Off)

<b>Analog Video Output Specifications</b>	<b>Detail</b>
Signal System	NTSC
Horizontal Resolution	700 TV lines (sharp mode) 650 TV lines (normal mode)
S/N Ratio	More than 55dB(AGC Off)

<b>General Specifications</b>	<b>Detail</b>
Dimensions (W x H x D)	ø3 1/8 inches x 4 3/8 inches (ø77 mm x 110 mm)
Power Requirements	AC 24 V ±10%, DC 12 V ±10%
Power Consumption	Max. 5.5W
Operating Temperature	14 °F to 122 °F (-10 °C to +50 °C)
Compression	N/A
FPS	N/A

## Resources

### Specification Sheet

<b>Description:</b>	<b>Release Date</b>	<b>Type/Size</b>
SSCCB564/CB574R Data Sheet		pdf / 316K

### Brochure

<b>Description:</b>	<b>Release Date</b>	<b>Type/Size</b>
Analog Camera Quick Reference Guide		pdf / 1,060K

### Product Manual

<b>Description:</b>	<b>Release Date</b>	<b>Type/Size</b>
SSC-CB564R/SSC-CB574R Operating Instructions		pdf / 1,518K