



**SSCN24A**  
Indoor IR Analog  
Minidome Camera  
with Vari-focal  
lens(3.7x), True Day  
Night and 650 TVL

**\$318.00**

U.S.List Price

UPC: 027242265424

**Overview**

Indoor IR Analog Minidome Camera with 2.8-10.5mm Vari-focal lens(3.7x), High sensitivity, True Day/Night, 650 TVL and AC24VDC12V

**Highlights**

- \* High resolution (650 TVL) and high sensitivity (0.15 lx color, 0.01 lx b/w, F1.2, 50 IRE)
- \* EXview CCD II 1/3-type CCD Sensor
- \* 3.7x variable focal lens with the focal length of 2.8 to 10.5mm
- \* Excellent S/N of 55dB, AGC OFF Weight ON
- \* Wide Range ATW of 2000° to 10000° K
- \* ATR-Lite (Adaptive Tone Reproduction) for gradation of the subjects to an optimum level, in order to see both high and dark areas effectively
- \* iBLC feature compensates for the exposure levels in dark scenes to improve the visibility of the subject
- \* ATW (Automatic Tracing White balance) automatically adjust the camera's white balance to adapt to changes in lighting conditions
- \* DSP "Effio-E" is able to provide a horizontal resolution of 650TVL with 12 bit A/D signal processing and various image enhancement technology

**Specifications**

Camera Specifications	Detail
IP/Analog	Analog
Image Device	1/3-type Super HAD CCD II
Horizontal Resolution	650 TV lines
Minimum Illumination	Color: 0.15lx, B/W: 0.01 lx (F1.2, 50 IRE) Color: 0.08 lx, B/W: 0.003 lx (F1.2, 30 IRE)
Lens Type	Built-in vari-focal lens
Focal Length	f=2.8 to 10.5 mm
F-Number	F1.2(Wide end), F2.6(Tele end)
Day Night	Yes(removable IR Filter)
Zoom Ratio	Optical 3.7x
Minimum Object Distance	11 7/8 inches (300mm)

White Balance Mode	ATW(2000K-10000K)/ATW-PRO(2500K-6500K)
Horizontal Viewing Angle	101.8 ° to 27.4 °
Gain	Auto(On/Off)
<b>Analog Video Output Specifications</b>	<b>Detail</b>
Signal System	NTSC
Horizontal Resolution	650 TV lines
S/N Ratio	More than 55dB(AGC Off)
<b>General Specifications</b>	<b>Detail</b>
Dimensions (W x H x D)	ø4 7/8 x 3 1/2 inches (ø121.6 x 86.5 mm)
Power Requirements	AC 24 V ±10%, DC 12 V ±10%
Power Consumption	1.7W
Operating Temperature	14 °F to 122 °F (-10 °C to +50 °C)
Compression	N/A
FPS	N/A
Resolution	650 TVL

## Accessories

### Optional Accessories

Model:	Description:	U.S.List Price
UNIWMB4	Gooseneck Wall Mount Bracket	\$80.00
UNICMA1	Corner Mount Adaptor to Allow Mounting Cameras in Outside Corners of a Building	\$125.00
UNIUMB1	Indoor Wall Mount Bracket	\$98.00
UNIWMBB1	Aluminum wall/pole mount back box	\$97.00
UNIPMA1	Pole Mount Adaptor to Allow Mounting Camera Housings to Poles	\$83.00
YTICB140	In-Ceiling Mount Kit for indoor mini domes cameras	\$98.00
YTICB600	In-Ceiling Mount Kit for indoor mini domes cameras	\$98.00
UNIMDPDH120	Pendant mount adaptor for indoor mini domes	\$95.00

## Resources

### Product Brochure

Description:	Release Date	Type/Size
SSCN24A Data Sheet		pdf / 545K

### Brochure

Description:	Release Date	Type/Size
Analog Camera Quick Reference Guide		pdf / 1,060K